

triton® Product Specification Sheet

Triton I400W Plunge Router

MOF001



Features

- Unique through-base bit changing system makes bit changes easy and fast.
- Winder handle plunge adjustment provides fast depth adjustment.
- Micro winder enables continuous fine depth adjustment through full plunge range.
- Push button plunge conversion activates conventional plunge mode.
- Compact size - perfect for hand-held use and table-mounting.
- Easy-set, direct reading 3 stage turret for precise preset cut depths.
- Safety switch shutter locks closed in bit-change mode to prevent power-on.
- Soft start and variable speed (with maintenance under load) provides the perfect speed for all cutter types.
- Removable plunge spring for easy bit adjustments when table-mounted.
- Fully enclosed guarding provides maximum protection from the cut zone.
- Dust port connects to any 38mm (1½") O.D. vacuum hose.
- Multi-function fence:
 - Extended base for greater stability.
 - Full fence adjustment for trenching etc.
 - Built-in circle cutter.

Specifications

MOTOR:	1400W. Soft start
INPUT:	230 - 240V ~ 50Hz
SPEED:	8,000 - 21,000min-1. Speed maintenance under load
COLLET:	½" with ¼" reducer
DEPTH ADJUSTMENT :	1. Winder handle rack and pinion 2. Micro winder 3. Conventional "free" plunge
BIT CHANGES:	Through-base, single spanner action. Auto shaft lock
GUIDE:	Extended baseplate with adjustable fence
WEIGHT:	4.7kg (10.4lb)
INSULATION CLASS:	Double insulated
OPTIONAL ACCESSORY KIT:	<ul style="list-style-type: none">• Table winder for fast, accurate height adjustments from above a router table.• Chip collector - provides effective chip extraction when performing edge work or using jigs (ie dovetail jigs).• Template guides - enable routing with jigs and templates.

