

triton Product Specification Sheet

Triton 1/2" Precision Router

TRA001



Features

Single spanner cutter changing **from above the table**. Shaft lock and power lock-off automatically engage in cutter change mode.

Fast plunge depth adjustment using winder handle. Full range fine depth adjustment via micro winder. Can also be quickly switched for conventional plunge mode.

Plunge spring is removable for lighter action.

Highly effective dust port.

Multi-function fence:

- Extended base for greater stability on edge work.
- Full trenching adjustment.
- Built-in circle cutter.

Well suited to table-mounting.

Specifications

MOTOR: 2400W (3¹/₄ hp). Soft start.

SPEED: 8,000 - 20,000 variable. Speed maintenance under load.

COLLET: 1/2" with 1/4" reducer.

DEPTH ADJUSTERS: 1. Winder handle rack & pinion
2. Micro winder
3. Conventional "free" plunge

BIT CHANGES: Through-base, single spanner action. Auto shaft lock.

GUIDE: Sole plate with adjustable fence.
Circle cutting feature.

GUARDING: Full front and rear safety shields.
Highly effective dust chute.

INPUT: 230 - 240V ~ 50/60Hz

WEIGHT: 6kg (13.2lb) approx.

TEMPLATE GUIDES: Optional kit available (TGA001)

OTHER FEATURES: Removable plunge spring for table-mounted use, easy set triple turret stops, illuminated switch with safety "lock-off" shutter.